

PS04 - Remove Epoxy Grout Haze

Remove Epoxy Grout Haze from Natural Stone & Porcelain Tiles

PRODUCT: **STRIP-IT™**

EQUIPMENT: AquaBug Cleaning Kit, Scrub pad or brush, broom, bucket, clean water and cotton towels. Optional: Scrub machine, wet-dry vac.



PRECAUTIONS:

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C and 32°C.
4. Do not mix with other chemicals or allow product to come in contact with any non-recommended surfaces;
5. Floor will get slippery during process. Take appropriate precautions to prevent slips or falls;
6. Will affect sealers, coatings, floor finishes & painted surfaces

PROCEDURE:

1. Sweep, vacuum, or wipe surface;
2. Use neat. Do **NOT** dilute;
3. Carefully apply liberal amount of **Strip-It™** to a small manageable area of up to 4m².
NOTE: Do **NOT** allow puddling in grout joints.
4. Spread with a roller, mop, sponge or brush;
5. Allow product to dwell no more than 30 minutes without drying;
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. Agitate with solvent resistant scrub pads, scrub brush or scrub machine;
8. Remove the residue with a wet vac or if thick, with clean, absorbent white cotton towels, scoop or shovel;
9. Rinse thoroughly with clean water;
10. Repeat the process as necessary;

NOTE: To help with residue removal, apply **XtremeClean™** diluted 1 part with 5 parts water to the surface after Step 9. Allow dwell time of 5-10 minutes then scrub or agitate. Remove with wet vac then rinse thoroughly. Allow to fully dry.

Note A: Epoxy Grout is formulated to be chemically resistant. The longer **Epoxy Grout Haze** is allowed to cure, the harder it will be to remove.

Note B: For some applications, the use of a Steam Gun after the 30 minute dwell time of **Strip-It** and just before the scrubbing process, can help with removing the **Epoxy Grout Haze**.

Note C: For cured or hard to remove **Epoxy Grout Haze**, contact Aqua-Seal STS Technical Services.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST.

KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES