

# PS19 - Create Anti Slip on Slippery Tiles

Create a Slip Resistant Surface on Porcelain , Tessellated & Ceramic Tiles

**PRODUCT:** **GRIP-IT T™**

**EQUIPMENT:** AquaBug Cleaning Kit, Scrub pad or brush, broom, bucket, clean water. cotton towels, calcium gluconate gel.



**PRECAUTIONS:**

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C & 32°C;
4. Do NOT allow product to come in contact with any non-recommended surfaces;
5. Do NOT mix with other chemicals or mix in metal buckets;
6. Do NOT mix with ammoniated cleaners as harmful fumes result.
7. Do NOT mix in metal buckets or containers;
8. Do NOT use on polished porcelain, acid sensitive or polished surfaces.
9. **Grip-It T™** creates a slip resistant microtexture. Colour can be affected the more texture that is created.

**PROCEDURE:**

1. Clean & prepare surface with **XtremeClean™** as per label directions - rinse thoroughly then allow to dry;
2. Sweep, vacuum or wipe for a clean, dry surface;
3. Pour **Grip-It T™** into a suitable plastic paint tray, bucket or container;
4. Carefully apply **Grip-It T™** evenly to surface with a suitable sponge, brush, natural bristle broom or mop;
5. **DO NOT POUR DIRECTLY FROM BOTTLE TO THE SURFACE;**
6. Allow to dwell for approx 5 minutes at a time - "dwell period";
7. **NEVER ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
8. After each "dwell period" test amount of slip resistance created by using your shoe in a scuffing motion in the standing **Grip-It T™** solution on the floor.
9. When desired level of slip resistance has been created, rinse thoroughly with clean water;
10. Repeat the process as necessary.

**NOTE:** To reduce soiling & staining, seal with appropriate penetrating type sealer from Aqua-Seal STS™ - refer to our website [www.aqua-seal.com.au](http://www.aqua-seal.com.au);

**SAFETY DIRECTIONS:**

**CORROSIVE**

1. Wear protective gloves, eye & skin protection when using.
2. Avoid breathing vapour or mist spray.
3. Avoid contact with skin & eyes.
4. May cause blindness & burns.
5. Burns might not be immediately painful or visible.
6. Obtain a supply of calcium gluconate gel
7. Wash tools, gloves & shoes thoroughly with clean water

**Note A:** Do NOT use **Grip-It T™** on Polished Porcelain, Acid Sensitive or Polished Surfaces.

**Note B:** **Grip-It T™** creates a slip resistant microtexture. Colour can be affected the more texture that is created.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

**READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST.**

**KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES**