

# PS01 - Remove Grout Haze - Light

## Remove Light Grout Haze from Porcelain or Ceramic Tiles

**PRODUCT:** **HAZE AWAY™**

**EQUIPMENT:** AquaBug Cleaning Kit, Scrub pad or brush, broom, bucket, clean water and cotton towels. Optional: Scrub machine, wet-dry vac.



**PRECAUTIONS:**

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow contact with any non-recommended surface;
5. May slightly dull some polished calcium based surfaces e.g. marble, limestone, travertine, cement based terrazzo

**PROCEDURE:**

1. Sweep, vacuum, or wipe surface;
2. Dilute **Haze Away™** as follows with clean water:
  - a) **LIGHT HAZE:** Dilute 1 part **Haze Away™** to 3 parts clean water;
  - b) **MODERATE HAZE:** Dilute 1 part **Haze Away™** to 2 parts clean water;
  - c) **HEAVY HAZE:** Dilute 1 part **Haze Away™** to 1 part clean water or use neat.
3. Carefully apply solution to surface with a sponge or mop;
4. Allow minimum dwell time of 10 minutes. Longer dwell time may be required.
5. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
6. Scrub with a white nylon pad or scrub machine;
7. Remove the dirty solution with a wet vac or mop;
8. Rinse thoroughly with clean water;
9. Repeat the process as necessary.

**Note:** Some areas may require longer dwell time and/or stronger solution.

**Note A:** Heavy grout haze or grout haze older than 10 days may require the use of **OxiTreat HD™**

**Note B:** Do not use **Haze Away™** on marble, limestone, travertine or on other acid-sensitive tile or stone.

**Note C:** Use **MicroScrub™** to remove grout haze from polished natural stone & acid sensitive surfaces - see **Problem Solver #3**.

**Note D:** For high solids latex modified grouts mixing a dilution of **OxiTreat HD™** and **Strip-It™** may be required. See **Problem Solver #4**

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST.

KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES

