

PS13 - Remove Enhance'N'Seal Residue

Remove Enhance'N'Seal Residue from Natural Stone & Porcelain Tiles

PURPOSE: Remove Uncured Enhance'N'Seal Residue or Within 48 hours of Application

PRODUCT: MICROSCRUB™

EQUIPMENT: AquaBug Cleaning Kit, Scrub pad or brush, broom, bucket, clean water and cotton towels. Optional: Scrub machine, wet-dry vac.



PRECAUTIONS:

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow product to contact any non-recommended surfaces;
5. Take care when using on dark coloured grout or stone;

PROCEDURE:

1. Sweep, vacuum, or wipe surface;
2. Slightly pre-wet surface & grout joints with clean water;
3. Pour approx 1-2 cups of MicroScrub™ to the pre-wet surface;
4. Scrub the surface with a white nylon pad, scrub brush or scrub machine;
5. For vertical surfaces, pre-wet surface by spraying water from a spray bottle then apply MicroScrub™ directly to a white nylon pad then scrub;
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. Remove the dirty solution with a wet vac or mop;
8. Rinse thoroughly with clean water;
9. Repeat as necessary.

PURPOSE: Remove Partial Cured Enhance'N'Seal Residue or After 48 hours of Application

PRODUCT: STRIP-IT™

EQUIPMENT: AquaBug Cleaning Kit, Scrub pad or brush, broom, bucket, clean water and cotton towels. Optional: Scrub machine, wet-dry vac.



PRECAUTIONS:

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C and 32°C.
4. Do not mix with other chemicals or allow product to come in contact with any non-recommended surfaces;
5. Floor will get slippery during process. Take appropriate precautions to prevent slips or falls;
6. Will affect Enhance'N'Seal, other sealers, coatings, floor finishes & painted surfaces

PROCEDURE:

1. Sweep, vacuum, or wipe surface;
2. Use neat. Do **NOT** dilute;
3. Carefully apply liberal amount of Strip-It™ to a small manageable area of up to 4m2.
4. Spread with a roller, mop, sponge or brush;
5. Allow product to dwell minimum 1 hour without drying or until coating or residue softens.
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. Agitate with solvent resistant scrub pads, scrub brush or scrub machine;
8. Remove the residue with a wet vac or if thick, with clean, absorbent white cotton towels, scoop or shovel;
9. Rinse thoroughly with clean water;
10. Repeat the process as necessary;

Note A: MicroScrub does not affect the performance of Enhance'N'Seal as it will only remove the uncured surface residue.

Note B: For heavy Enhance'N'Seal residue that has not cured, use Strip-It as per label instructions. You must then re-apply Enhance'N'Seal as per label instructions. Patchiness can occur.

Note C: For Enhance'N'Seal residue that has cured, contact Aqua-Seal STS Technical Services.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST.

KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES