

PS15 - Remove Algae, Mould, Mildew, Leaf & Tannins

Remove Algae, Mould, Mildew, Leaf Stains & Tannin from Natural Stone, Tiles, Concrete, Pavers etc

PRODUCT: **ACTIVE PLUS™**

- PRECAUTIONS:**
1. Always test first;
 2. Read entire label, SDS & technical bulletin before using;
 3. Wear appropriate skin & eye protection.
 4. Use when surface temperature is between 4°C & 32°C.
 5. Keep away from plants, soil and metals.
 6. Once mixed, do NOT cover or store mixed solution.
 7. Dispose any unused mixed solution after 4 hours by pouring into a drain or a toilet.



- PROCEDURE:**
1. Pre-wet the surface;
 2. Stir in 300gm of **Active Plus™** into a plastic bucket with 10 litres of clean, warm water; (For better results use hot water)
 3. Stir until it dissolves;
 4. Apply solution generously to surface and allow to dwell for 5-10 minutes (longer dwell time will give better results)
 5. **DO NOT ALLOW PRODUCT TO DRY ON SURFACE** (clean large areas in sections);
 6. Scrub with white nylon pad, broom or brush;
 7. Rinse thoroughly with clean water;
 8. Repeat as necessary.

PRODUCT: **OXITREAT HD™** - For very heavy build up

- PRECAUTIONS:**
1. Read entire label, SDS & technical bulletin before using;
 2. Wear appropriate skin & eye protection & use in a well ventilated area;
 3. Use when surface temperature is between 4°C & 32°C;
 4. Do not allow product to come in contact with non recommended surface;
 5. Do NOT use on acid sensitive/polished surfaces;
 6. Do NOT mix in metal buckets or containers;
 7. Remove all metal jewellery before using.



- PROCEDURE:**
1. Sweep, vacuum, or wipe surface;
 2. Slightly pre-wet surface with clean water;
 3. Dilute **OxiTreat HD™** depending on the severity of the problem:
 - a) **LIGHT:** Dilute 1 part **OxiTreat HD™** to 15 parts clean water.
 - b) **MODERATE:** Dilute 1 part **OxiTreat HD™** to 10 parts clean water.
 - c) **HEAVY:** Dilute 1 part **OxiTreat HD™** to 5 parts clean water
 - d) **EXTREME:** Dilute 1 part **OxiTreat HD™** to 3 parts clean water.
 4. Carefully apply the solution to surface with a sponge or a mop;
 5. Allow minimum dwell time of 10 minutes. Longer dwell time may be required.
 6. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
 7. Scrub with a white nylon pad or scrub machine;
 8. Remove the dirty solution with a wet vac or mop;
 9. Rinse thoroughly with clean water;
 10. Repeat the process as necessary.

Note 1: Heavily soiled areas may require longer dwell time and/or stronger solution.

Note 2: Add **MicroScrub™** to standing solution just prior to scrubbing to boost performance where required

Note A: Do not use **OxiTreat HD™** on marble, limestone, travertine or on other acid-sensitive tile or stone.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES

