

# Aqua-Seal Bronze+™

## Natural Look Sealer

### DESCRIPTION

Aqua-Seal Bronze+™ is a below surface sealer formulated to provide good stain resistance and keep a natural look on porous unsealed surfaces. Aqua-Seal Bronze+™ is water based, non flammable, non toxic, and NO VOC (0 grams/litre). Can also be used as a pre-grouting sealer. Allows excellent Moisture Vapour Transmission (MVT) For interior and exterior use.

### USES

Use on all natural stone, grout, porous ceramic and porcelain, terracotta, saltillo, quarry tiles, terrazzo, concrete, pavers and masonry surfaces where a natural look and good stain resistance is desired.

### TEST FIRST

Due to the nature of different surfaces, you should do several tests in inconspicuous areas according to the label instructions to determine application method, number of coats and desired results. The end user must determine the suitability of the product for their intended use.

### PRE-GROUT SEALING

This will allow quick and easy cleanup after grouting as grout may stain surfaces. Do not to saturate the open grout joints. Follow application instructions below.

### PRECAUTIONS

1. Always Test first;
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin and eye protection and use in a well ventilated area;
4. Surface must be clean and completely dry and free from any other sealers and coatings;
5. Use when surface temperature is between 4°C and 32°C.

### INSTRUCTIONS

1. Shake well before using.
2. Sweep, vacuum, or wipe surface;
3. Apply product using an Aqua-Seal Sealer Sponge, sealer applicator, paint pad or cotton towels;
4. After 5-10 minutes, remove any sealer visible on the surface by wiping the surface COMPLETELY DRY with absorbent paper or cotton towels. DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
5. If 2 or more coats are required, allow minimum 30 minutes between coats and follow label instructions for each coat;
6. The surface is ready for light traffic after 2 hours. Keep surface dry for 12 hours.

Note: 2 hours after the final coat, conduct a test to determine if the surface is properly sealed by applying a few water droplets to the surface. If the water is easily absorbed then apply an additional coat. Wait 2 hours and repeat the test.

### LIMITATIONS

- Do not allow the product to come in contact with any non-recommended surfaces;
- Regular use of harsh cleaners will affect the performance and longevity;
- Sealer will not prevent surface wear or etching from harsh chemicals.

### EXPECTED WEAR

Up to 5 years but will vary depending on texture and hardness of surface, surface wear plus frequency, and type of maintenance products used. Harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners and weather exposure will affect wear and performance. Re-seal as necessary.

### COVERAGE

Approximately 40-160m<sup>2</sup> per 4 litres per coat. The coverage will vary depending on density, porosity, texture, surface absorption, weather conditions, the application method and number of coats. As a guide: Porcelain Tile 160m<sup>2</sup>, Polished Granite 160m<sup>2</sup>, Sandstone 40-60m<sup>2</sup>, Honed Travertine 75-110m<sup>2</sup>. For full coverage chart refer to [www.aqua-seal.com.au](http://www.aqua-seal.com.au)

### MAINTENANCE

- Aqua-Seal STC™ EzyClean™ for routine, everyday cleaning;
- Aqua-Seal STC™ XtremeClean™ for periodic heavy duty cleaning;
- Aqua-Seal STC™ DeepClean Pro™ for large commercial areas.

### HANDLING AND STORAGE:

- Close container tightly after each use. Store in original container only.
- Store in temperatures between 4°C and 32°C.

### FIRST AID

For advice, contact a Poisons Information Centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of accident or if you feel unwell, seek medical advice immediately

### SAFETY DIRECTIONS

Avoid contact with skin and eyes.

### WARRANTY

Aqua-Seal STC™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST.