

Oxi-Treat HD™

Heavy Duty Acid Cleaner



DESCRIPTION & USE

OxiTreat HD™ is a fast acting concentrated acid treatment utilising an AQS™ Heavy Duty formula to remove most cement & grout haze, efflorescence, rust stains, mineral deposits, mortar residue & smears. Will help remove most hard water stains, lime deposits, soap scum and ground in dirt and grime. It will also etch concrete. **USE:** On ACID RESISTANT surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection & use in a well ventilated area;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow product to come in contact with non recommended surface;
5. Do **NOT** use on acid sensitive/polished surfaces;
6. Do **NOT** mix in metal buckets or containers;
7. Remove all metal jewellery before using.

APPLICATION INSTRUCTIONS:

1. Sweep, vacuum, or wipe surface;
2. Slightly pre-wet surface with clean water;
3. Dilute OxiTreat HD™ depending on the severity of the problem:
 - a) **LIGHT:** Dilute 1 part OxiTreat HD™ to 15 parts clean water.
 - b) **MODERATE:** Dilute 1 part OxiTreat HD™ to 10 parts clean water.
 - c) **HEAVY:** Dilute 1 part OxiTreat HD™ to 5 parts clean water
 - d) **EXTREME:** Dilute 1 part OxiTreat HD™ to 3 parts clean water.
4. Carefully apply the solution to surface with a sponge or a mop;
5. Allow minimum dwell time of 10 minutes. Longer dwell time may be required.
6. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
7. Scrub with a white nylon pad or scrub machine;
8. Remove the dirty solution with a wet vac or mop;
9. Rinse thoroughly with clean water;
10. Repeat the process as necessary.

Note 1: Heavily soiled areas may require longer dwell time and/or stronger solution.

Note 2: Add MicroScrub™ to standing solution just prior to scrubbing to boost performance where required

LIMITATIONS

- ▶ Does not remove deep set food, grease & oil stains. Refer to appropriate Aqua-Seal STS™ product by visiting our website www.aqua-seal.com.au
- ▶ Use MicroScrub™ to remove grout haze from polished natural stone & acid sensitive surfaces

COVERAGE

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use
- ▶ Store between 4°C and 32°C.
- ▶ Do not re-use container. Discard in rubbish
- ▶ Clean tools and hands with clean water.

FIRST AID

Contact a doctor or Poisons Information Centre (Australia Ph: 131-126, NZ Ph: 0800 764766). **Ingestion:** If swallowed, do NOT induce vomiting; Rinse mouth thoroughly with water and contact Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed. **Eyes:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. **DO NOT INTERRUPT FLUSHING.** If necessary, keep emergency vehicle waiting. Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses. **Skin & Hair:** Flush contaminated area with lukewarm, gently flowing water for at least 20-30 minutes. **DO NOT INTERRUPT FLUSHING.** If necessary, keep emergency vehicle waiting. Under running water, remove contaminated clothing, shoes and leather goods (eg watchbands and belts). If irritation persists, repeat flushing. **Inhalation:** First aid is not generally required. **General:** If irritation persists or feeling unwell, seek medical attention.

SAFETY DIRECTIONS: CORROSIVE

- ▶ Avoid contact with skin & eyes;
- ▶ Wear protective glasses and gloves when mixing or using;
- ▶ Do NOT kneel in this product. Avoid all skin contact.

Code	Size	Barcode Number
120-005	1ltr - OxiTreat HD	9347177001494
120-006	4 ltr - OxiTreat HD	9347177001500

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**