

PS26 - Recolour & Seal Grout

To create a uniform grout colour on faded or patchy or change the existing colour of grout and also seal the grout



PRODUCT: **RENUÉ'N'SEAL™**

- EQUIPMENT:**
- AquaBug Cleaning Kit;
 - Scrub pad or brush;
 - Broom
 - Bucket
 - Clean water;
 - Cotton towels.
 - Wet vac;
 - Optional: Scrub machine

- PRECAUTIONS:**
1. Read label, SDS & product technical bulletin before using;
 2. Wear appropriate skin and eye protection;
 3. Ensure that existing grout sits lower than the tile surface;
 4. Grout must be textured, clean & COMPLETELY dry and free from any other sealers & coatings;
 5. Use when surface temperature is between 4°C & 32°C;
 6. When using contrasting colours, more than 1 coat might be necessary with a drying time of 2 hours between each coat. Follow label "Application Instructions" for each coat;
 7. If using more than 1 bottle of a single colour, mix all the material to be used together in a large container to ensure uniform colour. Check batch numbers before starting;
 8. Textured or porous surfaces require more care when applying colorant. Check for ease of clean-up beforehand;
 9. For shower floors, the use of a moisture meter can help determine when the existing grout is COMPLETELY dry and ready to apply [Renue'N'Seal](#);

- PROCEDURE:**
1. SHAKE WELL BEFORE USING;
 2. Existing grout must be textured, clean & COMPLETELY dry;
 3. Sweep, vacuum, or wipe surface;
 4. Apply small amount of [Renue'N'Seal](#) directly onto grout joint;
 5. Work [Renue'N'Seal](#) along the grout joint in a back-forward motion using a Colourant Applicator or a kid size toothbrush;
 6. Ensure a thin even coat is applied and minimise the amount spread on to the surrounding tile surface then clean off;
 7. Ready for light traffic after 2 hours. Keep dry for a minimum 24 hours. Shower floors ok to use after 24-48 hour cure time.

CLEAN OFF INSTRUCTIONS - CLEAN UP-METHOD A:

Immediately wipe excess [Renue'N'Seal](#) from tile surface using a slightly damp chamois or sponge. Avoid wiping directly in grout joint.

CLEAN OFF INSTRUCTIONS - CLEAN UP-METHOD B:

Allow [Renue'N'Seal](#) to dry to the touch (Minimum 15-20 minutes but no longer than 2 hours) then mist a small amount of water on the surface. Using a white nylon pad, remove excess product from the tile surface, ensuring that you do not scrub directly into the grout joint;

Note A: Colour swatches on marketing material are only indicative & can vary due to printing & screen resolution;

Note B: Colour & shade variation can occur depending on batch, job site, lighting, surface and surrounding conditions;

Note C: Do not use in under water or pooling water situations or areas subject to hydrostatic pressure;

Note D: [Renue'N'Seal™](#) is NOT a waterproofing agent.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES