

Grout Release Pro™

Pre Grout Coating & Release



How it works: The Aqua Seal STS™ Product Trouble Shooting Guide covers the most common application issues and problems associated with each Aqua Seal STS™ product.

Problem: If the product problem you are experiencing is not covered by the Product Trouble Shooting Guide then it is most likely job specific. Please contact Aqua Seal STS™ direct for more detailed advice and information.

Solutions: The solutions described are not necessarily the only way to solve the specific problem. They are based on giving you the most efficient & direct solution without resorting to more complex solutions that may require a professional trades person. If the solutions outlined do not solve the problem it is most likely job specific. Please contact Aqua Seal STS™ direct for more detailed advice and information.

Note: Always read entire product label, SDS & product technical bulletin before using. Do a test area first.

Problem	Reason	Solution
Grout Release Pro hasn't been removed with the grouting process	<ul style="list-style-type: none"> Applied to heavy or for too long a period. Texture or porosity of tile, stone or grout absorbed too much product. 	<ul style="list-style-type: none"> Use XtremeClean at a stronger dilution and/or longer dwell time. Use Strip-It instead of XtremeClean as per label instructions.
Grout Release Pro still visible in grout joints or texture of tile & stone	<ul style="list-style-type: none"> Applied to heavy or for too long a period. Texture or porosity of tile, stone or grout absorbed too much product. 	<ul style="list-style-type: none"> Use a soft to medium nylon bristle brush when scrubbing Use XtremeClean at a stronger dilution and/or longer dwell time. Use Strip-It instead of XtremeClean as per label instructions.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES

